

## ICON-21 Low Sliding System Details

This system can be used when your spaces are limited and sliding horizontally therefore add attractiveness to your places. Curtain system can be applicable because of horizontally moving. Door and panel Locks are make safe your places when used. Panels are carrying each other when sliding first panel using with panel profiles between the panels.

### System Information

#### Profile system

- Optionally with or without vertical panel frames
- Parking variations is possible left, right or both side by no treshold bottom profile.
- 2 types of bottom and upper profiles are available. These are 3 and 5 rails.

#### Accessories

- All fittings are concealed within the profiles.
- Low-maintenance, non-corroding and failsafe fittings
- Inside and/or outside locking possible
- Left and right side locking possible owing to new desing locks
- Stainless steel and/or aluminium handles eligible optionally
- Optionally grey and black colour accessories are available
- Metal covers are standard

#### Assembly

- \* Every panel fitted low-maintenance and non-corrosing rollers.
- \* Polyamid coated and high quality rollers are used.
- \* Low noise, Low corrosion and high resistente to cold and hot effects

#### Sealing and ventilation

- The gap between the sliding panels are 2- 4 mm
- Using with aluminium profiles can be eliminate the gaps between the panels
- Brush gaskets are fitted horizontally at the top and at the vertical frame on the inside and outside
- This system is more suitable for partition of the offices and interior of the buildings.

#### Glazing

- 8 or 10 mm tempered safety glass panes
- Glass panels are fixed as safely to bottom of the panel profiles fasten with silicone adhesive.

#### Colour Options

- \* There are 4 kind of Standard colour options as ; Eloxal, white, wooden and pres (without colour)
- \* As an optional, able to paint with all the RAL colours.